


Transport equipment

Product data sheet

Article no.: 22601 Pallet dolly as tugger train



For pallets and lattice boxes in European standard sizes. Easy loading and unloading from the side with forklift. Sturdy sectional steel construction with 4 catch corners for stacking. Powder coated blue RAL 5007. 2 swivel and 2 fixed-wheel castors, with robust steel carriages suitable for tugger trains, wheels with PU tyres on aluminium rims, hubs with precision ball bearings. Swivel castors with wheel locks. Tyres are non-marking (trackless). Low-noise running on even flooring. Capacity 1000 kg. This coupling system guarantees the best possible directional stability. Tractors must have front wheel steering and tugger train drawbar! Max. 5 pallet dollies per train. Max. train speed 6 km/h. Max. train weight 3000 kg. Self-securing flat steel drawbar on the fixed-wheel side. Drawbar \varnothing 26.5 mm. Comfortable foot

Technical Details:



| | |
|--|---------------|
| Total load capacity (kg) | 1000 |
| Length of usable platform (mm) | 1210 |
| Width of usable platform (mm) | 810 |
| Height of loading platform (mm) | 290 |
| Total length (mm) | 1327 |
| Total width (mm) | 855 |
| Total height (mm) | 783 |
| Tyres | Polyurethane |
| Wheel size (mm) | 200 x 50 |
| Version | als Routenzug |
| Weight (kg) | 50 |
| Country of origin | Germany |
| Warranty (years) | 3 |
| Customs tariff number | 73269098 |
| GTIN | 4017976226019 |