1-92-Px Quick-adjustable standard pulling jaws (pair, clamping depth 100 mm)





DESCRIPTION

The pair of two quickly adjustable standard pulling jaws is suitable for 2-jaw universal pullers. The robust pulling jaws guarantee particularly safe pulling of bearings, gears, and discs. The green knurled knobs provide the highest operating comfort and allow quick, tool-free loosening or fastening of the pulling jaws - even with wet or oily hands.

RANGE OF APPLICATION

Suitable for 2-arm universal pullers

- Due to the freely movable pulling jaws sliding on the cross beam, eccentric components can also be pulled off.
- The knurling allows tool-free, quick loosening or repositioning of the pulling jaws.

MASTER DATA

GTIN [EAN] 4021176061257

Country of origin DF Case material Tool steel Series 2-Px 0,58 kg Net weight [kg] Package contents 1 few Packaging Act PAP 20


Yes (REACH, RoHS, POP, PROP65, Global sales capability given

TSCA)


APPLICATION IMAGE




DETAIL IMAGE



Quick-adjustable standard pulling jaws (pair, clamping depth 100 mm)




Abbreviation Attribut		Wert
A	Clamping depth outside pull-off [mm]	100 mm
K	Hook root thickness at the tip (claw thickness K) [mm]	3 mm
J	Hook base width (claw width J) [mm]	20 mm
0	Hook base depth usable (claw depth usable O) [mm]	15 mm
Н	Total hook root depth (total claw depth H) [mm]	31 mm
L	Total claw thickness (L+1mm) (claw distance to base surface) [mm]	10 mm
Z	Total length [mm]	132 mm



Abbrev	AbbreviationAttribut	
A	Clamping depth outside pull-off [mm]	100 mm
K	Hook root thickness at the tip (claw thickness K) [mm]	3 mm
J	Hook base width (claw width J) [mm]	20 mm
0	Hook base depth usable (claw depth usable O) [mm]	15 mm
Н	Total hook root depth (total claw depth H) [mm]	31 mm
L	Total claw thickness (L+1mm) (claw distance to base	10 mm
	surface) [mm]	
Z	Total length [mm]	132 mm



AbbreviationAttribut		Wert
A	Clamping depth outside pull-off [mm]	100 mm
K	Hook root thickness at the tip (claw thickness K) [mm]	3 mm
J	Hook base width (claw width J) [mm]	20 mm
0	Hook base depth usable (claw depth usable O) [mm]	15 mm
Н	Total hook root depth (total claw depth H) [mm]	31 mm
L	Total claw thickness (L+1mm) (claw distance to base surface) [mm]	10 mm
Z	Total length [mm]	132 mm



AbbreviationAttribut		Wert
A	Clamping depth outside pull-off [mm]	100 mm
K	Hook root thickness at the tip (claw thickness K) [mm]	3 mm

	Hook base width (claw width J) [mm]	20 mm
0	Hook base depth usable (claw depth usable O) [mm]	15 mm
Н	Total hook root depth (total claw depth H) [mm]	31 mm
L	Total claw thickness (L+1mm) (claw distance to base surface) [mm]	10 mm
Z	Total length [mm]	132 mm