1-192-Sx Quick-adjustable standard pulling jaws (set, clamping depth 200 mm)





The set of three quick adjustment standard jaws is suitable for 3-jaw universal pullers. The robust pulling jaws guarantee particularly safe pulling of bearings, gears, and discs. The green knurled knobs stand for maximum user comfort and enable quick, tool-free loosening or fastening of the pulling jaws, even with wet or oily hands.

RANGE OF APPLICATION

Suitable for 3-arm universal pullers

BENEFIT


- Due to the freely movable pulling jaws sliding on the cross beam, eccentric components can also be pulled off.
- Thanks to the knurling, a tool-free, quick release or movement of the pulling jaw is enabled.

MASTER DATA

GTIN [EAN] 4021176061196 Country of origin DE Case material Tool steel 2-Sx Series Net weight [kg] 1,86 kg Package contents 1 set Packaging Act

Yes (REACH, RoHS, POP, PROP65, Global sales capability given


DETAIL IMAGE



Quick-adjustable standard pulling jaws (set, clamping depth 200 mm)




AbbreviationAttribut		Wert
A	Clamping depth outside pull-off [mm]	200 mm
K	Hook root thickness at the tip (claw thickness K) [mm]	3 mm
J	Hook base width (claw width J) [mm]	20 mm
0	Hook base depth usable (claw depth usable O) [mm]	15 mm
Н	Total hook root depth (total claw depth H) [mm]	31 mm
L	Total claw thickness (L+1mm) (claw distance to base surface) [mm]	10 mm
Z	Total length [mm]	232 mm



AbbreviationAttribut		Wert
A	Clamping depth outside pull-off [mm]	200 mm
K	Hook root thickness at the tip (claw thickness K) [mm]	3 mm
J	Hook base width (claw width J) [mm]	20 mm
0	Hook base depth usable (claw depth usable O) [mm]	15 mm
Н	Total hook root depth (total claw depth H) [mm]	31 mm
	Total claw thickness (L+1mm) (claw distance to base	10 mm
	surface) [mm]	
Z	Total length [mm]	232 mm



AbbreviationAttribut		Wert
А	Clamping depth outside pull-off [mm]	200 mm
K	Hook root thickness at the tip (claw thickness K) [mm]	3 mm
J	Hook base width (claw width J) [mm]	20 mm
0	Hook base depth usable (claw depth usable O) [mm]	15 mm
Н	Total hook root depth (total claw depth H) [mm]	31 mm
L	Total claw thickness (L+1mm) (claw distance to base surface) [mm]	10 mm
Z	Total length [mm]	232 mm



AbbreviationAttribut		Wert
Α	Clamping depth outside pull-off [mm]	200 mm
K	Hook root thickness at the tip (claw thickness K) [mm]	3 mm

J	Hook base width (claw width J) [mm]	20 mm
C	Hook base depth usable (claw depth usable O) [mm]	15 mm
F	Total hook root depth (total claw depth H) [mm]	31 mm
L	Total claw thickness (L+1mm) (claw distance to base surface) [mm]	10 mm
Z	Total length [mm]	232 mm