1-250-P Standard pulling jaws (Pair, clamping depth 250 mm)





The pair of two standard jaws is suitable for 2-jaw universal pullers. The robust pulling jaws ensure particularly safe pulling of bearings,

RANGE OF APPLICATION

As a spare part for particularly safe pulling of bearings, gears and

BENEFIT

• Due to the freely movable pulling jaws sliding on the cross beam, eccentric components can also be pulled off.


MASTER DATA

GTIN [EAN] 4021176001901 Country of origin DE Case material Tool steel Series 0-P

1,36 kg Net weight [kg] Package contents 1 few Packaging Act

Yes (REACH, RoHS, POP, PROP65, Global sales capability given


DETAIL IMAGE



Standard pulling jaws (Pair, clamping depth 250 mm)




Abbreviation Attribut		Wert
A	Clamping depth outside pull-off [mm]	250 mm
K	Hook root thickness at the tip (claw thickness K) [mm]	3 mm
J	Hook base width (claw width J) [mm]	20 mm
0	Hook base depth usable (claw depth usable O) [mm]	15 mm
Н	Total hook root depth (total claw depth H) [mm]	31 mm
L	Total claw thickness (L+1mm) (claw distance to base surface) [mm]	10 mm
Z	Total length [mm]	282 mm



AbbreviationAttribut		Wert
A	Clamping depth outside pull-off [mm]	250 mm
K	Hook root thickness at the tip (claw thickness K) [mm]	3 mm
J	Hook base width (claw width J) [mm]	20 mm
0	Hook base depth usable (claw depth usable O) [mm]	15 mm
Н	Total hook root depth (total claw depth H) [mm]	31 mm
L	Total claw thickness (L+1mm) (claw distance to base surface) [mm]	10 mm
Z	Total length [mm]	282 mm



AbbreviationAttribut		Wert
A	Clamping depth outside pull-off [mm]	250 mm
K	Hook root thickness at the tip (claw thickness K) [mm]	3 mm
J	Hook base width (claw width J) [mm]	20 mm
0	Hook base depth usable (claw depth usable O) [mm]	15 mm
Н	Total hook root depth (total claw depth H) [mm]	31 mm
L	Total claw thickness (L+1mm) (claw distance to base surface) [mm]	10 mm
Z	Total length [mm]	282 mm



AbbreviationAttribut		Wert
A	Clamping depth outside pull-off [mm]	250 mm
K	Hook root thickness at the tip (claw thickness K) [mm]	3 mm

J	Hook base width (claw width J) [mm]	20 mm
0	Hook base depth usable (claw depth usable O) [mm]	15 mm
Н	Total hook root depth (total claw depth H) [mm]	31 mm
L	Total claw thickness (L+1mm) (claw distance to base surface) [mm]	10 mm
Z	Total length [mm]	282 mm