# 1-250-S Standard pulling jaws (set, clamping depth 250 mm)





# DESCRIPTION

The set of three standard jaws is suitable for 3-jaw universal pullers. The robust pulling jaws ensure particularly safe pulling of bearings,

### **RANGE OF APPLICATION**

As a spare part for particularly safe pulling of bearings, gears and

### **BENEFIT**

- Thanks to the freely moving pulling jaws sliding on the cross beam, even eccentric components can be pulled off.


### **MASTER DATA**

GTIN [EAN] 4021176002083

Country of origin DE Case material Tool steel Series 0-S 2,04 kg Net weight [kg] Package contents 1 set Packaging Act PAP 21

Yes (REACH, RoHS, POP, PROP65, Global sales capability given


## **DETAIL IMAGE**



# Standard pulling jaws (set, clamping depth 250 mm)




Abbreviation Attribut		Wert
A	Clamping depth outside pull-off [mm]	250 mm
K	Hook root thickness at the tip (claw thickness K) [mm]	3 mm
J	Hook base width (claw width J) [mm]	20 mm
0	Hook base depth usable (claw depth usable O) [mm]	15 mm
Н	Total hook root depth (total claw depth H) [mm]	31 mm
L	Total claw thickness (L+1mm) (claw distance to base surface) [mm]	10 mm
Z	Total length [mm]	282 mm



AbbreviationAttribut		Wert
A	Clamping depth outside pull-off [mm]	250 mm
K	Hook root thickness at the tip (claw thickness K) [mm]	3 mm
J	Hook base width (claw width J) [mm]	20 mm
0	Hook base depth usable (claw depth usable O) [mm]	15 mm
Н	Total hook root depth (total claw depth H) [mm]	31 mm
L	Total claw thickness (L+1mm) (claw distance to base surface) [mm]	10 mm
Z	Total length [mm]	282 mm



AbbreviationAttribut		Wert
А	Clamping depth outside pull-off [mm]	250 mm
K	Hook root thickness at the tip (claw thickness K) [mm]	3 mm
J	Hook base width (claw width J) [mm]	20 mm
0	Hook base depth usable (claw depth usable O) [mm]	15 mm
Н	Total hook root depth (total claw depth H) [mm]	31 mm
L	Total claw thickness (L+1mm) (claw distance to base surface) [mm]	10 mm
Z	Total length [mm]	282 mm



AbbreviationAttribut		Wert
A	Clamping depth outside pull-off [mm]	250 mm
K	Hook root thickness at the tip (claw thickness K) [mm]	3 mm

J	Hook base width (claw width J) [mm]	20 mm
0	Hook base depth usable (claw depth usable O) [mm]	15 mm
Н	Total hook root depth (total claw depth H) [mm]	31 mm
L	Total claw thickness (L+1mm) (claw distance to base surface) [mm]	10 mm
Z	Total length [mm]	282 mm