1-400-S Standard pulling jaws (set, clamping depth 400 mm)





DESCRIPTION

The set of three standard jaws is suitable for 3-jaw universal pullers. The robust pulling jaws ensure particularly safe pulling of bearings, gears, and discs.

RANGE OF APPLICATION

As a spare part for particularly safe pulling of bearings, gears and discs

BENEFIT

 Thanks to the freely moving pulling jaws sliding on the cross beam, even eccentric components can be pulled off.

MASTER DATA

 GTIN [EAN]
 4021176975684

 Country of origin
 DE

 Case material
 Tool steel

 Series
 0-S


Net weight [kg] 3,48 kg
Package contents 1 set
Packaging Act PP 05

Global sales capability given

Yes (REACH, RoHS, POP, PROP65,

TSCA)


DETAIL IMAGE



Standard pulling jaws (set, clamping depth 400 mm)




Abbreviation Attribut		Wert
A	Clamping depth outside pull-off [mm]	400 mm
K	Hook root thickness at the tip (claw thickness K) [mm]	3 mm
J	Hook base width (claw width J) [mm]	20 mm
0	Hook base depth usable (claw depth usable O) [mm]	15 mm
Н	Total hook root depth (total claw depth H) [mm]	31 mm
L	Total claw thickness (L+1mm) (claw distance to base surface) [mm]	10 mm
Z	Total length [mm]	432 mm



AbbreviationAttribut		Wert
A	Clamping depth outside pull-off [mm]	400 mm
K	Hook root thickness at the tip (claw thickness K) [mm]	3 mm
J	Hook base width (claw width J) [mm]	20 mm
0	Hook base depth usable (claw depth usable O) [mm]	15 mm
Н	Total hook root depth (total claw depth H) [mm]	31 mm
L	Total claw thickness (L+1mm) (claw distance to base	10 mm
	surface) [mm]	
Z	Total length [mm]	432 mm



AbbreviationAttribut		Wert
A	Clamping depth outside pull-off [mm]	400 mm
K	Hook root thickness at the tip (claw thickness K) [mm]	3 mm
	Hook base width (claw width J) [mm]	20 mm
0	Hook base depth usable (claw depth usable O) [mm]	15 mm
Н	Total hook root depth (total claw depth H) [mm]	31 mm
L	Total claw thickness (L+1mm) (claw distance to base surface) [mm]	10 mm
Z	Total length [mm]	432 mm



AbbreviationAttribut		Wert
A	Clamping depth outside pull-off [mm]	400 mm
K	Hook root thickness at the tip (claw thickness K) [mm]	3 mm

J	Hook base width (claw width J) [mm]	20 mm
0	Hook base depth usable (claw depth usable O) [mm]	15 mm
Н	Total hook root depth (total claw depth H) [mm]	31 mm
L	Total claw thickness (L+1mm) (claw distance to base surface) [mm]	10 mm
Z	Total length [mm]	432 mm