

28-B 19-piece slide hammer set Ø 12-40 mm



DESCRIPTION

The 19-piece slide hammer set 28-B is used for non-contact extraction of internal bearings, bearing outer rings, and bushings as well as components with threads (dowel pins, keys, bolts, etc.) in craft, workshop, and industry. The multi-shell design of the internal extractors with their extra large gripping edges allows for the safe extraction of internal parts. The included slide hammer is used together with the internal extractors. Additionally, there are thread inserts in the set for extracting parts with central threaded holes, which are used together with the slide hammer.

RANGE OF APPLICATION

For non-contact extraction of internal bearings, bearing outer rings and bushings as well as components with threads (dowel pins, feather keys, bolts, etc.)

BENEFIT

- Application-oriented compilation for universal use
- By storing them in the box, the completeness of the set can be easily viewed.
- The internal extractor, together with the slide hammer and thread inserts, is capable of finding a suitable response in versatile pulling situations.
- The slide hammer allows for optimal and safe pulling due to its design
- Thread inserts allow internal extraction even where concentric threaded holes would prevent ordinary internal extraction.
- With the help of the laser-engraved dimensions on the thread adapters, threads can be clearly identified in practice

OPERATION

- Determine the internal diameter of the ball bearing and select the appropriate internal extractor.
- Insert the internal extractor into the bore and tighten the stop nut.
- If a supporting surface is available, choose the counter stay; otherwise, choose the slide hammer.
- Screw the slide hammer rod onto the wedge spindle of the internal extractor.
- Use the slide hammer with impact motion to extract the bearing.

MASTER DATA

GTIN [EAN]	4021176507786
Country of origin	DE
Case material	Tool steel
Series	28-A/B
Net weight [kg]	6,145 kg
Package contents	1 set
Packaging Act	PAP 21
Global sales capability given	Yes (REACH, RoHS, POP, PROP65, TSCA)

SPARE PARTS

- 21-1_2-jaw internal extractors
- 21-2_2-jaw internal extractors
- 21-3_2-jaw internal extractor
- 21-4_2-jaw internal extractors
- 21-5_Two-shell internal extractors
- 22-0-17_Slide hammer device with 1.7 kg impact weight
- GA12-1815_reducing piece

APPLICATION IMAGE



DETAIL IMAGE



- GA7-10_Reducer
- GE10-1815_Thread insert
- GE12-1815_Thread insert
- GE14-1815_Thread insert
- GE16-1815_Thread insert
- GE18-1815_Thread insert
- GE20-1815_Thread insert
- GE22-1815_Thread insert
- GE24-1815_Thread insert
- GE8-1815_Thread insert