

40-5 Hub puller with cross beam, impact/shock model, for bolt circles up to 225 mm diameter, 5 pulling jaw



DESCRIPTION

The hub puller with cross beam is used for pulling hubs on trucks. The spindle runs in an axially movable threaded bushing, in case blows to the spindle head are required to loosen the hub. The freely movable T-handle on the spindle head guarantees manual tightening of the spindle in tight spaces.

RANGE OF APPLICATION

For pulling off wheel hubs on trucks

BENEFIT

- Protection of wheel bolts through always planar-fitting nut recesses
- Integrated, free-moving T-handle guarantees manual spindle drive in tight spaces

OPERATION

- Fix the pulling jaw to the wheel hub using a screw connection
- Manually pull the spindle to apply pressure
- Move the T-handle on the spindle head until the wheel hub is released

MASTER DATA

GTIN [EAN]	4021176014956
Country of origin	DE
Case material	Tool steel
Series	40
Net weight [kg]	5,44 kg
Package contents	1 piece
Packaging Act	PAP 21
Global sales capability given	Yes (REACH, RoHS, POP, PROP65, TSCA)

SPARE PARTS

- 04030005_Complete plate with bushing
- 40-3-1_Pulling jaws (pair)
- 40-3-8_Hammer crank for hub puller
- 626181_Spindle