

800 Short hydraulic spindle, up to 10 t tension force (thread size)



DETAIL IMAGE



DESCRIPTION

The grease hydraulic spindle of the 800 series is the motor of the puller and achieves an average tension force of 20 t. With this, particularly stubborn bearings, gears and discs can be effortlessly dismantled. As a true powerhouse, the spindle impresses with its compact design, easy applicability, and portable use. The spindle is ribbed on the sides to provide a particularly good grip for the fingers during readjustment. Due to its favorable installation dimensions, the spindle can be used universally. Thanks to integrated grease hydraulics, no external pump is required.

RANGE OF APPLICATION

For effortless removal of especially tight bearings, gears, and discs.

BENEFIT

- The hydraulic spindle guarantees easy and controlled pulling of particularly tight-fitting parts with minimal effort
- The hydraulic spindle doubles the manual pulling force by 100%
- Handy format for quick, portable use

MASTER DATA

GTIN [EAN]	4021176034343
Country of origin	DE
Case material	Tool steel
Series	800
Net weight [kg]	1,46 kg
Package contents	1 piece
Packaging Act	PAP 21
Global sales capability given	Yes (REACH, RoHS, POP, PROP65, TSCA)

SPARE PARTS

- 610075_Spindle
- 800-ERS_Wear part set
- 800-REP_Factory overhaul No. 800
- 800017_Spindle pressure piece
- ERS-OIL_Hydraulic oil